

### W3. Winkel mit Kupplung

W3. Angle with Coupling



**Zink/Ms vernickelt  
mit Pg-Gewinde  
Schutzart IP 68 bis 10 bar  
Art.-Gruppe: W3.**

*Zinc/Brass nickel plated,  
Pg connection thread  
Type of protection IP 68 up to 10 bar  
Art.-group: W3.*

Abb. 1  
Fig. 1




Abb. 2  
Fig. 2

| Anschlussgewinde/-länge<br>Connection thread/-length |      | Artikel-Nummer<br>Art.-No. |      |         |      |         |    |
|------------------------------------------------------|------|----------------------------|------|---------|------|---------|----|
| A                                                    | D mm |                            | C mm | E mm    | F mm | SW      |    |
| Pg 9                                                 | 6,0  | 9 EF                       | 34   | Pg 9    | 23   | 17x18,9 | 25 |
| Pg 11                                                | 6,0  | 11 EF                      | 40   | Pg 11   | 28   | 20x22,2 | 25 |
| Pg 13,5                                              | 6,5  | 13 EF                      | 42   | Pg 13,5 | 30   | 22x24,4 | 25 |
| Pg 16                                                | 6,5  | 16 EF                      | 43   | Pg 16   | 32   | 24x26,7 | 25 |
| Pg 21                                                | 7,0  | 21 EF                      | 54   | Pg 21   | 39   | 30x33,5 | 10 |
| Pg 29                                                | 8,0  | 29 EF                      | 69   | Pg 29   | 46   | 40x43,5 | 5  |

### W5. Kupplung

W5. Coupling



**Ms vernickelt, mit metrischem Anschlussgewinde EN 60 423 oder Pg-Gewinde  
Schutzart IP 68  
Art.-Gruppe: W5.**

*Brass nickel plated, metric connection thread EN 60 423 or Pg thread  
Type of protection IP 68  
Art.-group: W5*

Abb. 1  
Fig. 1

#### Verschraubungskörper

Gland body

| Werkstoff<br>Material | Ausführung<br>Execution                 | Bestellschlüssel<br>Art.-No. supplement |
|-----------------------|-----------------------------------------|-----------------------------------------|
| Ms<br>Brass           | galv. vernickelt<br>galv. nickel plated | -<br>-                                  |



**Kupplung, Ms vernickelt, zum Ausrichten und Montieren von vorkonfektionierten Kabel- und Schlauchverschraubungen oder Winkeln.**

*Coupling, brass nickel plated, to align and install  
harnessed cable and hose glands or angles*




Abb. 2  
Fig. 2

| Nenngröße<br>Rated size |      | Artikel-Nummer<br>Art.-No. |      |      |           | Schlüsselweite<br>Spanner width |  |
|-------------------------|------|----------------------------|------|------|-----------|---------------------------------|--|
| A                       | D mm |                            | C mm | E mm | SW x E mm |                                 |  |
| Pg 9                    | 6,0  | 9 MEF                      | 14   | 9,0  | 17x18,9   | 25                              |  |
| Pg 11                   | 6,5  | 11 MEF                     | 14   | 12,0 | 20x22,2   | 25                              |  |
| Pg 13,5                 | 6,5  | 13 MEF                     | 14   | 12,0 | 22x24,4   | 25                              |  |
| Pg 16                   | 6,5  | 16 MEF                     | 16   | 15,0 | 24x26,7   | 25                              |  |
| Pg 21                   | 7,0  | 21 MEF                     | 18   | 18,5 | 30x33,5   | 25                              |  |
| Pg 29                   | 8,0  | 29 MEF                     | 19   | 25,0 | 40x43,5   | 10                              |  |