嘉尼企業股份有限公司 CANAL ELECTRONIC CO.,LTD.



CHARACTERISTICS	
OPERATING FORCE:	110gf MAX.
DIFFERENTIAL FORCE:	
RELEASE FORCE:	35gf MIN.
FREE POSITION:	
OPERATING POSITION:	15.3± 0.5MM.
PRE-TRAVEL:	1.6MM MAX.
DIFFERENTIAL TRAVEL:	0.4MM MAX.
OVER-TRAVEL:	0.8MM MIN.
FULL OVERTRAVEL FORCE:	

ELECTRICAL DATA	
CONTACT ARRANGEMENT	
S.P.D.T	
	10(2)A 125/250VAC 0.5A 125VDC 0.25A 250VDC 40T85 μ 2E4
	10.1A 1/10HP 125/250VAC 0.5A 125VDC 0.25A 250VDC

NOTES:
1. MOUNTING HOLES WILL ACCEPT 3.0 MAX PINS OR SCREWS.
2. DEGREE OF PROTECTION: IEC IP67

REVISION	DESCRIPION	REVISED BY
4		
3		
2		
1 2014.07.10	首次出圖	張俊雄

TOLEANCES .X .XX ANGLE ½°				UNIT	mm	PART NAME	SPEC DRAWING	DWG NO
DRAWN BY	張俊雄	DESIGNED BY	王豐文	SCALE				WS2499A
CHECKED BY	Jimmy	APPROVED BY		DATE	2014.07.10	PART NO	G5W11-WZ100A01-W3	