

UT206



[Enlarge](#)



Registered Design No.: 0011438. 1M001

[Download Manual](#)

Digital Clamp Multimeters

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	400mV/4V/40V/400V/600V	$\pm (0.8\%+1)$
AC Voltage	4V/40V/400V/600V	$\pm (1.2\%+5)$
AC Current	400A/1000A	$\pm (2\%+5)$
Resistance	400W/4kW/40kW/400kW/4MW/40MW	$\pm (1\%+2)$
Capacitance	4nF/40nF/400nF/4mF/40mF/200mF	$\pm (3\%+5)$
Temperture($^{\circ}\text{C}$)	-40 $^{\circ}\text{C}$ ~1000 $^{\circ}\text{C}$	$\pm (1\%+3)$
Frequency	10Hz ~ 10MHz	$\pm (0.1\%+3)$
Duty Cycle	0.1% - 99.9%	✓
Special Functions		
Auto Ranging		✓
Diode		✓
Continuity Buzzer		✓
Relative Mode		✓
Data Hold		✓
Display Backlight		✓
Full Icon Display		✓
Sleep Mode		✓
Jaw Opening Light		✓
Max. Jaw Size	40mm	✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	Around 10MW	✓
Max. Display	3999	✓

GENERAL CHARACTERISTICS

Power	9V Battery (6F22), 3V Battery (AAAx2)
LCD Size	52 x 27mm
Product Colour	Body-Grey, Jaw-Red
Product Net Weight	540g (excluding tool box)
Product Size	260 x 90 x 45mm
Standard Accessories	Test Lead, English Manual, Batteries, Point Contact Temperature Probe, Tool Box
Optional Accessories*	Clip-On Test Lead Light(UT-TL), Built-In Test Lead Light(UT-L1), Built-In Test Lead Light Plus(UT-L2), Carrying Bag
Standard Packing	Gift Box
Standard Quantity Per Carton	20 pcs
Standard Carton Measurement	591 x 370 x 474 mm (0.104 CBM Per Standard Carton)
Standard Carton Gross Weight	27.6kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.

[Back to main menu](#)