


Warystory typu JVR-14N

SPECIFICATION

Part No	Maximum allowable Voltage		Maximum Energy		Withstanding Surge Current		Rated Wattage	Varistor Voltage	Maxiumum Clamping Voltage	Typical Capacitance (reference)
	ACrms (V)	DC (V)	(10/1000us) (J)	(2ms) (J)	1 time	2 times				
					(A)					
WA 14N0910k	550	745	217.0	155.0	4500	2500	0.6	910	1500	220
WA 14N0820k	510	670	203.0	145.0				820	1355	240
WA 14N0780k	485	640	203.0	145.0				780	1290	260
WA 14N0750k	460	615	203.0	145.0				750	1240	270
WA 14N0680k	420	560	168.0	120.0				680	1120	290
WA 14N0620k	385	505	168.0	120.0				620	1025	320
WA 14N0560k	350	460	149.8	107.0				560	920	360
WA 14N0510k	320	415	149.8	107.0				510	845	390
WA 14N0470k	300	385	149.8	107.0				470	775	430
WA 14N0430k	275	350	145.6	104.0				430	710	460
WA 14N0390k	250	320	134.4	96.0				390	650	510
WA 14N0360k	230	300	123.2	88.0				360	595	560
WA 14N0330k	210	275	112.0	80.0				330	550	610
WA 14N0300k	190	250	103.6	74.0				300	500	670
WA 14N0270k	175	225	93.8	67.0				270	455	740
WA 14N0240k	150	200	82.6	59.0				240	395	830
WA 14N0220k	140	180	79.8	57.0				220	360	900
WA 14N0200k	130	170	79.8	57.0				200	340	1000
WA 14N0180k	115	150	58.8	42.0				180	300	1100
WA 14N0150k	95	125	51.8	37.0				150	250	1300
WA 14N0120k	75	100	40.6	29.0				120	200	1700
WA 14N0100k	60	85	33.6	24.0				100	165	2000
WA 14N0082k	50	65	29.4	21.0				82	135	2400
WA 14N0068k	40	56	23.8	17.0	1000	500	0.1	68	#135	2900
WA 14N0056k	35	45	19.6	14.0				56	#110	3600
WA 14N0047k	30	38	16.8	12.0				47	#93	4300
WA 14N0039k	25	31	13.2	9.4				39	#77	5100
WA 14N0033k	20	26	12.3	8.8				33	#65	6100
WA 14N0027k	17	22	9.7	6.9				27	#53	7400
WA 14N0022k	14	18	7.6	5.4				22	#43	9100
WA 14N0018L	11	14	6.6	4.7				18	#36	11100

DIMENSIONS

DIMENSIONS(mm)	Model No.	T MAX.	D MAX.	H MAX.	d.	E±0.8	L MIN.
	WA 14N0018L	4.6	17	20	0.8	7.5	20
	WA 14N0068k	5.3					
	WA 14N0082k	4.5	17	20	0.8	7.5	20
	WA 14N0470k	6.5					
	WA 14N0510k	6.5	17	20	0.8	7.5	20
	WA 14N0910k	9.7					