


Berna 5050 SMD led flex strip-60leds/m



Introduction

The flexible light strip uses high-brightness 5050 SMD LEDs. With its flexible shape it can be molded into any configuration and is perfect for decorative lighting, cove lighting and architectural lighting.


Applications

- Architectural decorative lighting,archway,canopy and bridge edge lighting
- Show case,cabinet,cove lighting, bench,backlight


Benefits


- Continuous length flexible LED light strips
- Long life-time with minimum maintenance required
- Colors available: red,green,blue.amber,pink,RGB color-changing,white.
- Runs on 12v systems like solar cell charged batteries
- 120-degree wide angle illumination
- Vibration proof/waterproof (optional) and retains stable performance in tough environment

Demension(mm):



Specification







Model	Color	Wavelen	Len	LED	Light Output	Light	Beam	Voltage	Current	Max. Power
Number		gth(nm)	gth(Q'ty	(mcd)	Output	Angle	(V DC)	(A)	Consumption
			m)			(lumen)	(degrees)			(W)
BN-FS-R		620-625	5	300	300x1800	1800	120	12	6	72
BN-FS -Y		585-590	5	300	300x1800	1800	120	12	6	72
BN-FS -B		460-465	5	300	300x820	1500	120	12	6	72
BN-FS -G		520-525	5	300	300x3300	2200	120	12	6	72
BN-FS -W		6000K	5	300	300x5000	5100	120	12	6	72
BN-FS -WW		3000K	5	300	300x3900	4950	120	12	6	72

Waterproofing Grade:



1P20: Non-waterproof, cann't touch water during usage

 $IP65: \ \ Silicon\ glue\ with\ coated,\ surface\ can\ touch\ water-drops\ during\ usage$

1P68: Silicon tube with silicon glue inside, can totally put into water

Packing details:

• Sticked with 3M tape

• Packed in 5meters/reel & each reel packed in anti-static bag

• Weight: IP20: 0.14kg/reel; IP65: 0.26kg/reel; IP68: 0.46kg/reel.

Berna Lighting Limited

ADD: 3rd Floor, Building A, Weijian Industrial park, Tangtou Industrial Zone, Shiyan Town, Bao'an District, Shenzhen, China

TEL: 86-755-29516559 FAX: 86-755-29516559

 $EMAIL: sales@berna-led.com \\ \qquad http://www.bernaled.com$