

Features

Model	Designation	Rating	Type of switch enclosed & contact arrangement	Cable type/length	Contact	Action Force	Material of Rind
CFS-101	Standard Type Momentary Action	10A 250VAC	Mirco-switch momentary	0.75mm2,3C/0.5 meter,1 meter~3 meter	1A1B	1.2 kg	Plastics Aluminum cast
CFS-102		15A 250VAC	CM1704	0.75mm2,3C/1 meter,1.5 meter~2meter	1A1B	1.1 kg	
CFS-3		10A 250VAC	Mirco-switch momentary 2pcs.	0.75mm2,6C/1meter,1 meter~3 meter	2A2B	1.2 kg	
CFS-3S		15A 250VAC	CM1704	0.75mm2,6C/1 meter,1 meter~2 meter	2A2B	1.1 kg	
CFS-105	Standard Type Alternate Action	6A 250VAC	Imported alternative switch	0.75mm2,2C/1 meter,1 meter~2 meter	PUSH ON PUSH OFF	2 kg	Plastics Aluminum cast
CFS-106		6A 250VAC	Imported Micro-switch	0.75mm2,3C/1 meter	PUSH 1A PUSH 1B	1.5 kg	
CFS-201	Mini Foot Switch Front End Push	10A 250VAC	Micro-switch Momentary	0.5mm2,3C/1 meter~3 meter	1A1B	0.7 kg	Plastics
CFS-01		10A 250VAC		0.5mm2,3C/1 meter~3 meter	1A1B	0.7 kg	
CFS-1		10A 250VAC		0.5mm2,3C/1 meter~3 meter	1A1B	0.9 kg	
CFS-302	Protective Guard Foot Switch	15A 250VAC	CM1704	Accessory: Cable gland (No cable)	1A1B	3.2 kg	Plastics and Aluminum cast
CFS-305		6A 250VAC	Push butoom switch alternate action		PUSH ON PUSH OFF	3.1 kg	
CFS-306		6A 250VAC	Imported micro-switch		PUSH 1A PUSH 1B	3.5 kg	
CFS-402	Large Type	15A 250VAC	CM1704		1A1B	3.2 kg	

NOTES:

- Add R for waterproof, available in CFS3 & CFS4.
- Add Z for aluminum housing, available in CFS1, CFS# & CFS4.

Appearance and dimension

