SOLDERING IRON LEAD-FREE SOLDERING SYSTEM

**Exso**

LEAD-FREE SOLDERING SYSTEM

LedSol 300

220V ESD Pb-free

- The Heater & the sensor are integrated in the tip.(patent no.0037616)
- Excellent Thermal Recovery Performance using PID control.
- LCD with Backlight is employed for better visuals.
- Soldering Iron of Quick-type is employed for convenient tip change.
- Setting Temperature is protected by your password.
- Working time is displayed(1ch).
- Auto SleepMode.
- Auto Power-off.

Temperature Graph

— LedSol 300-1(1ch)

Temperature (℃)

[Measurement condition]
* To contact 100mm lead-free solder
* Arrival Time after setting 350℃

Model	LedSol 300-1	LedSol 300-2
Input Voltage	AC 220V, 60Hz(or 50Hz)	
Heater Output	24V AC, 75W	24V AC, 75W×2
Power Consumption	80W	160W
Temperature Control	100~500℃(212~932°F)	
Weight	2.33kg	2.77kg
Dimensions	108.5(W)×132(H)×126.5(D)mm	

LCD Display

LedSol30◇-2

LedSol-50

LedSol-30

ETW-30 (option)

ELD Tip

ELD

B	ELD-B	ELD-B2	ELD-BI
ELD-1C	ELD-2C	ELD-3C	ELD-4C	ELD-5C
ELD-1.2D	ELD-1.6D	ELD-2D	ELD-2D	ELD-2.4D	ELD-3D
ELD-4D	ELD-5.2D	ELD-6D
ELD-TI	ELD-TI2	ELD-TI3	ELD-3.5KF	ELD-5KF	ELD-775KF
ELD-3J	ELD-4J	ELD-5J	ELD-6J	ELD-6JO	ELD-4VI