

Palm Size Digital Multimeters UT33B, UT33C, UT33D

Specifications	Range	Best Accuracy		
Model		UT33B	UT33C	UT33D
DC Voltage (V)	200mV/2000mV/20V/200V/500V	$\pm(0.5\%+2)$	$\pm(0.5\%+2)$	$\pm(0.5\%+2)$
AC Voltage (V)	200V/500V	$\pm(1.2\%+10)$	$\pm(1.2\%+10)$	$\pm(1.2\%+10)$
DC Current (A)	200 μ A/200mA/10A	$\pm(1\%+2)$		
	2000 μ A/20mA/200mA/10A		$\pm(1\%+2)$	$\pm(1\%+2)$
Resistance (Ω)	200 Ω /2000 Ω /20k Ω /200k Ω /20M Ω	$\pm(0.8\%+2)$	$\pm(0.8\%+2)$	
	200 Ω /2000 Ω /20k Ω /200k Ω /20M Ω /200M Ω			$\pm(0.8\%+2)$
Temperature ($^{\circ}$ C)	-40 $^{\circ}$ C 1000 $^{\circ}$ C		$\pm(1\%+3)$	
Temperature ($^{\circ}$ F)	-40 $^{\circ}$ F 1832 $^{\circ}$ F		$\pm(1\%+4)$	
Features				
Display Count		2000	2000	2000
Manual Range		√	√	√
Battery Test	1.5V/9V/12V	$\pm(2.5\%+2)$		
Square Wave Output				√
Diode		√	√	√
Continuity Buzzer			√	√
Low Battery Indication		√	√	√
Data Hold		√	√	√
LCD Backlight		√	√	√
Input Impedance for DCV	Around 10M Ω	√	√	√
General Characteristic				
Power	9V Battery 6F22)			
LCD Size	48mm×16mm			
Product Color	Red and Grey			
Product Net Weight	179g (Including Holster)			
Product Size	130mm×73.5mm×35mm			
Standard Accessories	UT33B/UT33D-Battery, Test Lead,Holster			
	UT33C-Battery, Test Lead,Holster,Point Contact Temperature Probe			
Standard Individual Packing	Gift Box, English Manual			
Standard Quantity Per Carton	60 PCs			
Standard Carton Measurement	490mm×356mm×315mm (0.055 CBM Per Standard Carton)			
Standard Carton Gross Weight	UT33B/UT33D-18 Kg UT33C-20 Kg			