


Gegenmuttern Kunststoff

Synthetic lock nuts

Anschlussgewinde metrisch | Entry thread metric



Material: Polyamid
glasfaserverstärkt
Ausführung: 6-kant
Einsatztemperatur: -40°C / +100°C

Material: Polyamide glass fiber
reinforced
Execution: Hexagonal design
Temperature range: -40°C / +100°C



Hellgrau RAL 7035			Light grey RAL 7035		
G		M	Art.-Nr. Art. no.		
M12x1.5	17	5.5	8212	100	
M16x1.5	22	5.5	8217	100	
M20x1.5	26	6.5	8220	100	
M25x1.5	32	7.0	8225	100	
M32x1.5	41	7.0	8232	100	
M40x1.5	50	7.0	8240	50	
M50x1.5	60	8.5	8250	10	



Schwarz RAL 9005			Black RAL 9005		
G		M	Art.-Nr. Art. no.		
M12x1.5	17	5.5	8212.40	100	
M16x1.5	22	5.5	8217.40	100	
M20x1.5	26	6.5	8220.40	100	
M25x1.5	32	7.0	8225.40	100	
M32x1.5	41	7.0	8232.40	100	
M40x1.5	50	7.0	8240.40	50	
M50x1.5	60	8.5	8250.40	10	

Anschlussgewinde Pg | Entry thread Pg



Hellgrau RAL 7035			Light grey RAL 7035		
G		M	Art.-Nr. Art. no.		
Pg 7	19	5.0	8207	100	
Pg 9	22	6.0	8209	100	
Pg 11	24	6.0	8211	100	
Pg 13	27	6.0	8213	100	
Pg 16	30	6.0	8216	100	
Pg 21	36	7.0	8221	100	
Pg 29	46	7.0	8229	50	
Pg 36	60	8.0	8236	25	
Pg 42	65	8.0	8242	25	
Pg 48	70	8.0	8248.48	25	



Schwarz RAL 9005			Black RAL 9005		
G		M	Art.-Nr. Art. no.		
Pg 7	19	5.0	8207.40	100	
Pg 9	22	6.0	8209.40	100	
Pg 11	24	6.0	8211.40	100	
Pg 13	27	6.0	8213.40	100	
Pg 16	30	6.0	8216.40	100	
Pg 21	36	7.0	8221.40	100	
Pg 29	46	7.0	8229.40	50	
Pg 36	60	8.0	8236.40	25	
Pg 42	65	8.0	8242.40	25	
Pg 48	70	8.0	8248.48.40	25	