



ISSUE 11; February 2012 - RoHS 2011/65/EU

Description

- Industry standard package
Suitable for real time clock applications
Plastic encapsulated

Frequency Range

- Frequency 32.768kHz
- Frequency Tolerance ± 20 ppm

General Specification

- Load Capacitance (CL) 12.5pF Standard
- Drive Level 1.0 μ W max
- Ageing ± 5 ppm max per year @ 25°C
- Shunt Capacitance (C0) 1pF typ

Operable Temperature Range

- -40 to 85°C

Environmental Parameters

- Operable Temperature Range: -40 to 85°C
- Storage Temperature Range: -55 to 125°C
- Drop: 75cm drop (3 times) onto hard wooden board
- Vibration: 1.5mm amplitude, 10Hz-60Hz, 2-3mins in 3 mutually perpendicular planes, duration 2hrs each plane

Ordering Information (*minimum required)

- Frequency*
- Model*
- Tolerance @25°C
- Load Capacitance*


Example

32.768kHz 91SMX

20/-/12.5

Packing Details


- Pack Style: **Bulk** Loose in bulk pack
Pack Size 100
- Pack Style: **Reel** Tape and reel in accordance with EIA-481-D
Pack Size 2,000
- Alternative packing options available

**Outline (mm)****Sales Office Contact Details:**

UK: +44 (0)1460 270200
Germany: +49 (0)7264 9145-0

France: +33 (0)5 34 50 91 18
USA: +1 (0) 408 455 2426

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com

**Typical Frequency Stability Characteristics****Electrical Specification - maximum limiting values**

Frequency Range	Frequency Tolerance	Typical Frequency Stability Coefficient	Temperature Range	ESR Max	Vibration Mode
32.768kHz	±20ppm	-0.035ppm/°C²	-40 to 85°C	50kΩ	Tuning Fork

This document was correct at the time of printing; please contact your local sales office for the latest version

Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: +49 (0)7264 9145-0

France: +33 (0)5 34 50 91 18
USA: +1 (0) 408 455 2426

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com