

D1238L12B/S

1. MODEL NUMBER	D1238L12B(H1)	D1238L12S(H1)
2. CATEGORY	BRUSHLESS DC FAN	BRUSHLESS DC FAN
3. FRAME SIZE	120 × 120 × 38 mm (4.7 × 4.7 × 1.5 inch)	120 × 120 × 38 mm (4.7 × 4.7 × 1.5 inch)
4. RATED VOLTAGE	12 VDC	12 VDC
5. OPERATING VOLTAGE RANGE	9 V ~15V	9 V ~15V
6. START-UP VOLTAGE	9 V / Min.	9 V / Min.
7. RATED MOTOR SPEED	1950 RPM ±10%	1950 RPM ±10%
8. AIR FLOW	76 CFM (2.15 m ³ /Min.)	76 CFM (2.15 m ³ /Min.)
9. STATIC PRESSURE	3.17 mm/H ₂ O (0.12 inch/H ₂ O)	3.17 mm/H ₂ O (0.12 inch/H ₂ O)
10. RATED CURRENT	0.24 Amp ±10%	0.24 Amp ±10%
11. RATED INPUT POWER	2.88 Watts ±10%	2.88 Watts ±10%
12. NOISE LEVEL	32.9 dB(A)	32.9 dB(A)
13. DIRECTION OF ROTATION	Clockwise viewed from front label	Clockwise viewed from front label
14. OPERATING TEMPERATURE	-10°C ~ + 70°C / 66% (RH)	-10°C ~ + 70°C / 66% (RH)
15. STORAGE TEMPERATURE	-40°C ~ + 75°C / 66% (RH)	-40°C ~ + 75°C / 66% (RH)
16. BEARING SYSTEM	BALL BEARING	SLEEVE BEARING
17. LIFE EXPECTANCY	70,000 Hrs	30,000 Hrs
18. SAFETY APPROVAL	UL, CUL, TUV, CE	UL, CUL, TUV, CE
19. WEIGHT	297 gm	297 gm

