

D2010M05B/S

1. MODEL NUMBER	D2010M05B(H1)	D2010M05S(H1)
2. CATEGORY	BRUSHLESS DC FAN	BRUSHLESS DC FAN
3. FRAME SIZE	20 x 20 x 10 mm (0.8 x 0.8x 0.4 inch)	20 x 20 x 10 mm (0.8 x 0.8x 0.4 inch)
4. RATED VOLTAGE	5 VDC	5 VDC
5. OPERATING VOLTAGE RANGE	4 V ~ 5.5V	4 V ~ 5.5V
6. START-UP VOLTAGE	4 V / Min.	4 V / Min.
7. RATED MOTOR SPEED	11500 RPM $\pm 10\%$	11500 RPM $\pm 10\%$
8. AIR FLOW	0.8 CFM (0.02 m ³ /Min.)	0.8 CFM (0.02 m ³ /Min.)
9. STATIC PRESSURE	2.05 mm/H ₂ O (0.08 inch/H ₂ O)	2.05 mm/H ₂ O (0.08 inch/H ₂ O)
10. RATED CURRENT	0.14 Amp $\pm 10\%$	0.14 Amp $\pm 10\%$
11. RATED INPUT POWER	0.70 Watts $\pm 10\%$	0.70 Watts $\pm 10\%$
12. NOISE LEVEL	26 dB(A)	26 dB(A)
13. DIRECTION OF ROTATION	Clockwise viewed from front label	Clockwise viewed from front label
14. OPERATING TEMPERATURE	-10°C ~ + 70°C / 66% (RH)	-10°C ~ + 70°C / 66% (RH)
15. STORAGE TEMPERATURE	-40°C ~ + 75°C / 66% (RH)	-40°C ~ + 75°C / 66% (RH)
16. BEARING SYSTEM	BALL BEARING	SLEEVE BEARING
17. LIFE EXPECTANCY	70,000 Hrs	30,000 Hrs
18. SAFETY APPROVAL	UL, CUL, TUV, CE	UL, CUL, TUV, CE
19. WEIGHT	6 gm	6 gm

