

D4010H24B/S

1. MODEL NUMBER	D4010H24B(X1)	D4010H24S(X1)
2. CATEGORY	BRUSHLESS DC FAN	BRUSHLESS DC FAN
3. FRAME SIZE	40 x 40 x 10 mm (1.6 x 1.6 x 0.40 inch)	40 x 40 x 10 mm (1.6 x 1.6 x 0.40 inch)
4. RATED VOLTAGE	24 VDC	24 VDC
5. OPERATING VOLTAGE RANGE	12.0 V ~ 27.6V	12.0 V ~ 27.6V
6. START-UP VOLTAGE	12.0 V / Min.	12.0 V / Min.
7. RATED MOTOR SPEED	7000 RPM ±10%	7000 RPM ±10%
8. AIR FLOW	7.9 CFM (0.22 m ³ /Min.)	7.9 CFM (0.22 m ³ /Min.)
9. STATIC PRESSURE	3.7 mm/H ₂ O (0.15 inch/H ₂ O)	3.7 mm/H ₂ O (0.15 inch/H ₂ O)
10. RATED CURRENT	0.09 Amp ±10%	0.09 Amp ±10%
11. RATED INPUT POWER	2.16 Watts ±10%	2.16 Watts ±10%
12. NOISE LEVEL	33 dB(A)	33 dB(A)
13. DIRECTION OF ROTATION	Clockwise viewed from front label	Clockwise viewed from front label
14. OPERATING TEMPERATURE	-10°C ~ + 70°C / 66% (RH)	-10°C ~ + 70°C / 66% (RH)
15. STORAGE TEMPERATURE	-40°C ~ + 75°C / 66% (RH)	-40°C ~ + 75°C / 66% (RH)
16. BEARING SYSTEM	BALL BEARING	SLEEVE BEARING
17. LIFE EXPECTANCY	70,000 Hrs	30,000 Hrs
18. SAFETY APPROVAL	UL, CUL, TUV, CE	UL, CUL, TUV, CE
19. WEIGHT	16 gm	16 gm

