

D4020L24B/S

1. MODEL NUMBER	D4020L24B(X1)	D4020L24S(X1)
2. CATEGORY	BRUSHLESS DC FAN	BRUSHLESS DC FAN
3. FRAME SIZE	40 × 40 × 20 mm (1.6 × 1.6 × 0.8inch)	40 × 40 × 20 mm (1.6 × 1.6 × 0.8 inch)
4. RATED VOLTAGE	24 VDC	24 VDC
5. OPERATING VOLTAGE RANGE	12 V ~ 27V	12 V ~ 27V
6. START-UP VOLTAGE	12V / Min.	12 V / Min.
7. RATED MOTOR SPEED	5000 RPM ±10%	5000 RPM ±10%
8. AIR FLOW	5.3 CFM (0.15 m ³ /Min.)	5.3 CFM (0.15 m ³ /Min.)
9. STATIC PRESSURE	2.74 mm/H ₂ O (0.11 inch/H ₂ O)	2.74 mm/H ₂ O (0.11 inch/H ₂ O)
10. RATED CURRENT	0.04 Amp ±10%	0.04 Amp ±10%
11. RATED INPUT POWER	0.96 Watts ±10%	0.96 Watts ±10%
12. NOISE LEVEL	21.23 dB(A)	21.23 dB(A)
13. DIRECTION OF ROTATION	Clockwise viewed from front label	Clockwise viewed from front label
14. OPERATING TEMPERATURE	-10°C ~ + 70°C / 66% (RH)	-10°C ~ + 70°C / 66% (RH)
15. STORAGE TEMPERATURE	-40°C ~ + 75°C / 66% (RH)	-40°C ~ + 75°C / 66% (RH)
16. BEARING SYSTEM	BALL BEARING	SLEEVE BEARING
17.LIFE EXPECTANCY	70,000 Hrs	30,000 Hrs
18. SAFETY APPROVAL	UL, CUL, TUV, CE	UL, CUL, TUV, CE
19. WEIGHT	29 gm	29 gm

