

D6010L05B/S

1. MODEL NUMBER	D6010L05B(X1)	D6010L05S(X1)
2. CATEGORY	BRUSHLESS DC FAN	BRUSHLESS DC FAN
3. FRAME SIZE	60 x 60 x 10 mm (2.4 x 2.4 x 0.4 inch)	60 x 60 x 10 mm (2.4 x 2.4 x 0.4 inch)
4. RATED VOLTAGE	5 VDC	5 VDC
5. OPERATING VOLTAGE RANGE	3.5 V ~ 5.5V	3.5 V ~ 5.5V
6. START-UP VOLTAGE	3.5V / Min.	3.5V / Min.
7. RATED MOTOR SPEED	3000 RPM $\pm 10\%$	3000 RPM $\pm 10\%$
8. AIR FLOW	12.0 CFM (0.34 m ³ /Min.)	12.0 CFM (0.34 m ³ /Min.)
9. STATIC PRESSURE	1.84 mm/H ₂ O (0.07 inch/H ₂ O)	1.84 mm/H ₂ O (0.07 inch/H ₂ O)
10. RATED CURRENT	0.17 Amp $\pm 10\%$	0.17 Amp $\pm 10\%$
11. RATED INPUT POWER	0.85 Watts $\pm 10\%$	0.85 Watts $\pm 10\%$
12. NOISE LEVEL	23.83 dB(A)	23.83 dB(A)
13. DIRECTION OF ROTATION	Clockwise viewed from front label	Clockwise viewed from front label
14. OPERATING TEMPERATURE	-10°C ~ + 70°C / 66% (RH)	-10°C ~ + 70°C / 66% (RH)
15. STORAGE TEMPERATURE	-40°C ~ + 75°C / 66% (RH)	-40°C ~ + 75°C / 66% (RH)
16. BEARING SYSTEM	BALL BEARING	SLEEVE BEARING
17. LIFE EXPECTANCY	70,000 Hrs	30,000 Hrs
18. SAFETY APPROVAL	UL, CUL, TUV, CE	UL, CUL, TUV, CE
19. WEIGHT	23 gm	23 gm

