D6015L12B/S		
1. MODEL NUMBER	D6015L12B(X1)	D6015L12S(X1)
2. CATEGORY	BRUSHLESS DC FAN	BRUSHLESS DC FAN
3. FRAME SIZE	60 x 60 x 15 mm (2.4 x 2.4 x 0.6 inch)	60 x 60 x 15 mm (2.4 x 2.4 x 0.6 inch)
4. RATED VOLTAGE	12 VDC	12 VDC
5. OPERATING VOLTAGE RANGE	9 V ~ 15V	9 V ~ 15V
6. START-UP VOLTAGE	9 V / Min.	9 V / Min.
7. RATED MOTOR SPEED	3500 RPM ±10%	3500 RPM ±10%
8. AIR FLOW	13.7 CFM (0.39 m^3/Min.)	13.7 CFM (0.39 m^3/Min.)
9. STATIC PRESSURE	2.23 mm/H_2O (0.09 inch/H_2O)	2.23 mm/H_2O (0.09 inch/H_2O)
10. RATED CURRENT	0.11 Amp ±10%	0.11 Amp ±10%
11. RATED INPUT POWER	1.32 Watts ±10%	1.32 Watts ±10%
12. NOISE LEVEL	24.61 dB(A)	24.61 dB(A)
13. DIRECTION OF ROTATION	Clockwise viewed from front label	Clockwise viewed from front label
14. OPERATING TEMPERATURE	-10°C ~ + 70°C / 66% (RH)	-10°C ~ + 70°C / 66% (RH)
15. STORAGE TEMPERATURE	-40°C ~ + 75°C / 66% (RH)	-40°C ~ + 75°C / 66% (RH)
16. BEARING SYSTEM	BALL BEARING	SLEEVE BEARING
17.LIFE EXPECTANCY	70,000 Hrs	30,000 Hrs
18. SAFETY APPROVAL	UL, CUL, TUV, CE	UL, CUL, TUV, CE
19. WEIGHT	34 gm	34 gm

