

D8015H12B/S

1. MODEL NUMBER	D8015H12B(X1)	D8015H12S(X1)
2. CATEGORY	BRUSHLESS DC FAN	BRUSHLESS DC FAN
3. FRAME SIZE	80 x 80 x 15 mm (3.1 x 3.1 x 0.6 inch)	80 x 80 x 15 mm (3.1 x 3.1 x 0.6 inch)
4. RATED VOLTAGE	12VDC	12VDC
5. OPERATING VOLTAGE RANGE	9 V ~ 15V	9 V ~ 15V
6. START-UP VOLTAGE	9 V / Min.	9 V / Min.
7. RATED MOTOR SPEED	3000 RPM $\pm 10\%$	3000 RPM $\pm 10\%$
8. AIR FLOW	30.2 CFM (0.86 m ³ /Min.)	30.2 CFM (0.86 m ³ /Min.)
9. STATIC PRESSURE	2.66 mm/H ₂ O (0.10 inch/H ₂ O)	2.66 mm/H ₂ O (0.10 inch/H ₂ O)
10. RATED CURRENT	0.17 Amp $\pm 10\%$	0.17 Amp $\pm 10\%$
11. RATED INPUT POWER	2.28 Watts $\pm 10\%$	2.28 Watts $\pm 10\%$
12. NOISE LEVEL	31.06 dB(A)	31.06 dB(A)
13. DIRECTION OF ROTATION	Clockwise viewed from front label	Clockwise viewed from front label
14. OPERATING TEMPERATURE	-10°C ~ + 70°C / 66% (RH)	-10°C ~ + 70°C / 66% (RH)
15. STORAGE TEMPERATURE	-40°C ~ + 75°C / 66% (RH)	-40°C ~ + 75°C / 66% (RH)
16. BEARING SYSTEM	BALL BEARING	SLEEVE BEARING
17. LIFE EXPECTANCY	50,000 Hrs	25,000 Hrs
18. SAFETY APPROVAL	UL, CUL, TUV, CE	UL, CUL, TUV, CE
19. WEIGHT	40 gm	40 gm

