

D9225L12B/S		
1. MODEL NUMBER	D9225L12B(X1)	D9225L12S(X1)
2. CATEGORY	BRUSHLESS DC FAN	BRUSHLESS DC FAN
3. FRAME SIZE	92 x 92 x 25 mm (3.6 x 3.6 x 1.0 inch)	92 x 92 x 25 mm (3.6 x 3.6 x 1.0 inch)
4. RATED VOLTAGE	12 VDC	12 VDC
5. OPERATING VOLTAGE RANGE	9 V ~15V	9 V ~15V
6. START-UP VOLTAGE	9 V / Min.	9 V / Min.
7. RATED MOTOR SPEED	2000 RPM $\pm 10\%$	2000 RPM $\pm 10\%$
8. AIR FLOW	39 CFM (1.10 m ³ /Min.)	39 CFM (1.10 m ³ /Min.)
9. STATIC PRESSURE	1.76 mm/H ₂ O (0.07 inch/H ₂ O)	1.76 mm/H ₂ O (0.07 inch/H ₂ O)
10. RATED CURRENT	0.16 Amp $\pm 10\%$	0.16 Amp $\pm 10\%$
11. RATED INPUT POWER	1.92 Watts $\pm 10\%$	1.92 Watts $\pm 10\%$
12. NOISE LEVEL	24.58 dB(A)	24.58 dB(A)
13. DIRECTION OF ROTATION	Clockwise viewed from front label	Clockwise viewed from front label
14. OPERATING TEMPERATURE	-10°C ~ + 70°C / 66% (RH)	-10°C ~ + 70°C / 66% (RH)
15. STORAGE TEMPERATURE	-40°C ~ + 75°C / 66% (RH)	-40°C ~ + 75°C / 66% (RH)
16. BEARING SYSTEM	BALL BEARING	SLEEVE BEARING
17. LIFE EXPECTANCY	70,000 Hrs	30,000 Hrs
18. SAFETY APPROVAL	UL, CUL, TUV, CE	UL, CUL, TUV, CE
19. WEIGHT	85 gm	85 gm

