

Terminals Series

KLS8-01106 Female pre-insulating Terminals Series

Maximum Electrical Rating: 75°C 300 Volts Max.
Insulation Material: Vinyl
Terminal Material: Brass

VIII



| Item No. | Conductor cross-section | Nema tab mm | Thickness of material: T mm | Dimension | | | | | Color |
|------------------|--|----------------|--------------------------------|-----------|---------|---------|---------|--------------|-------|
| | | | | B mm | d mm | D mm | L mm | H mm | |
| FDD1. 25-110 (5) | 0.5~1.5mm ² (22~16A. W. G.) I Max=10A | 0.5*2.8 | 0.3 | 3.8 | 1.7 | 3.8 | 19 | 10 Red | |
| FDD1. 25-110 (8) | | 0.8*2.8 | 0.3 | 3.8 | 1.7 | 3.8 | 19 | | |
| FDD1. 25-187 (5) | | 0.5*4.75 | 0.35 | 5.6 | 1.7 | 3.8 | 19 | | |
| FDD1. 25-187 (8) | | 0.8*4.75 | 0.35 | 5.6 | 1.7 | 3.8 | 19 | | |
| FDD1. 25-205 | | 0.5*5.2 | 0.35 | 6.5 | 1.7 | 3.8 | 20 | | |
| FDD1. 25-250 | | 0.8*6.35 | 0.4 | 7.4 | 1.7 | 3.8 | 21 | | |
| FDD2-110 (5) | 1.5~2.5mm ² (16~14A. W. G.) I Max=15A | 0.5*2.8 | 0.3 | 3.8 | 2.3 | 4.3 | 19.0 | 10 Blue | |
| FDD2-110 (8) | | 0.8*2.8 | 0.3 | 3.8 | 2.3 | 4.3 | 19.0 | | |
| FDD2-187 (5) | | 0.5*4.75 | 0.35 | 5.6 | 2.3 | 4.3 | 19.0 | | |
| FDD2-187 (8) | | 0.8*4.75 | 0.35 | 5.6 | 2.3 | 4.3 | 19.0 | | |
| FDD2-205 | | 0.8*5.2 | 0.35 | 6.4 | 2.3 | 4.3 | 20.0 | | |
| FDD2-250 | | 0.8*6.35 | 0.4 | 7.4 | 2.3 | 4.3 | 21 | | |
| FDD2-312 | | 0.8*8.0 | 0.4 | 9 | 2.3 | 4.3 | 23.0 | | |
| FDD5. 5-250 | 4~6mm ² (12~10A. W. G.) I Max=24A | 0.5*6.35 | 0.4 | 7.4 | 3.4 | 5.7 | 25.0 | 14 Yellow | |
| FDD5. 5-375 | | 1.2*9.4 | 0.5 | 10.9 | 3.4 | 5.7 | 29.6 | | |

ORDER INFORMATION

KLS8-01106 - FDD1. 25 - 110 (5)

