

YUMO

I can start everything...
— 工控开关方案解决专家 —

ABS16系列金属按钮 Metal Buttons Switch Series



YUMO ELECTRIC



YUMO ELECTRIC

ABS16系列金属按钮 Metal Buttons Switch Series

YUMO

I can start everything...
— 工控开关方案解决专家 —

Φ16金属按钮开关 Metal Push Button Switch


ABS16S-P1



技术参数/Parameter

安装尺寸Diameter: Φ 16mm
开关额定值Switch Rating: 3A/250VAC
开关组合Contact Configuration: 1NO
操作类型Operation Type: 自复型Momentary
头部形状The Front Shape: 平面 Flat
外壳材料The Crust Material:
不锈钢Stainless steel/铜镀铬Copper plating
防护等级IP Degree: IP67, IK10

外形尺寸/Size




ABS16S-Q1



技术参数/Parameter

安装尺寸Diameter: Φ 16mm
开关额定值Switch Rating: 3A/250VAC
开关组合Contact Configuration: 1NO
操作类型Operation Type: 自复型Momentary
头部形状The Front Shape: 球面 Ball
外壳材料The Crust Material:
不锈钢Stainless steel/铜镀铬Copper plating
防护等级IP Degree: IP67, IK10

外形尺寸/Size




ABS16S-G1



技术参数/Parameter

安装尺寸Diameter: Φ 16mm
开关额定值Switch Rating: 3A/250VAC
开关组合Contact Configuration: 1NO
操作类型Operation Type: 自复型Momentary
头部形状The Front Shape: 高头 High
外壳材料The Crust Material:
不锈钢Stainless steel/铜镀铬Copper plating
防护等级IP Degree: IP67, IK10

外形尺寸/Size




ABS16S-P0



技术参数/Parameter

安装尺寸Diameter: Φ 16mm
开关额定值Switch Rating: 3A/250VAC
开关组合Contact Configuration: 1NO
操作类型Operation Type: 自复型Momentary
头部形状The Front Shape: 平面 Flat
外壳材料The Crust Material:
不锈钢Stainless steel/铜镀铬Copper plating
防护等级IP Degree: IP67, IK10

外形尺寸/Size




ABS16S-Q0



技术参数/Parameter

安装尺寸Diameter: Φ 16mm
开关额定值Switch Rating: 3A/250VAC
开关组合Contact Configuration: 1NO
操作类型Operation Type: 自复型Momentary
头部形状The Front Shape: 球面 Ball
外壳材料The Crust Material:
不锈钢Stainless steel/铜镀铬Copper plating
防护等级IP Degree: IP67, IK10

外形尺寸/Size




ABS16S-G0



技术参数/Parameter

安装尺寸Diameter: Φ 16mm
开关额定值Switch Rating: 3A/250VAC
开关组合Contact Configuration: 1NO
操作类型Operation Type: 自复型Momentary
头部形状The Front Shape: 高头 High
外壳材料The Crust Material:
不锈钢Stainless steel/铜镀铬Copper plating
防护等级IP Degree: IP67, IK10

外形尺寸/Size



Φ16金属按钮开关 Metal Push Button Switch


ABS16S-P1-E



技术参数/Parameter

安装尺寸Diameter: Φ 16mm
灯珠颜色Color:
开关额定值Switch Rating: 3A/250VAC
开关组合Contact Configuration: 1NO
操作类型Operation Type: 自复型Momentary
头部形状The Front Shape: 平面 Flat
带灯方式Lamp type: 环形带灯Ring Illuminated(LED)
外壳材料The Crust Material:
不锈钢Stainless steel/铜镀铬Copper plating
防护等级IP Degree: IP67, IK10

外形尺寸/Size




ABS16S-G1-E



技术参数/Parameter

安装尺寸Diameter: Φ 16mm
灯珠颜色Color:
开关额定值Switch Rating: 3A/250VAC
开关组合Contact Configuration: 1NO
操作类型Operation Type: 自复型Momentary
头部形状The Front Shape: 高头 High
带灯方式Lamp type: 环形带灯Ring Illuminated(LED)
外壳材料The Crust Material:
不锈钢Stainless steel/铜镀铬Copper plating
防护等级IP Degree: IP67, IK10

外形尺寸/Size



ABS16S-C1-E



技术参数/Parameter

安装尺寸Diameter: Φ 16mm
灯珠颜色Color:
开关额定值Switch Rating: 3A/250VAC
开关组合Contact Configuration: 1NO
操作类型Operation Type: 自复型Momentary
头部形状The Front Shape: 平面 Flat
带灯方式Lamp type: 电源符号带灯Power symbol illuminated(LED)
外壳材料The Crust Material:
不锈钢Stainless steel/铜镀铬Copper plating
防护等级IP Degree: IP67, IK10

外形尺寸/Size

