



Recommend hole size

NOTES:

- \* Zinc alloy die cast housing and cylinder, bright chrome plated.
  - \* 5 disc tumbler mechanism.
  - \* Reversible double-bitted brass keys, nickel plated.
  - \* Silver plated contacts and terminals.
  - \* S286A 2 position (OFF-ON) 4 terminals.(2NO 2NC)
  - \* All keyed alike.(KA#2801)
  - \* Meet with ROHS.
- SPECIFICATION:
- \* Contact Rating: 2A 125 VAC.
  - \* Contact Resistance: 10 Milli-Ohms Max.
  - \* Insulation Resistance: 500 Meg-Ohms Min.(500VDC)
  - \* Dielectric Strength: 1000 VAC - 1 Minute.

		DRAWN	DATE
0.000°±0.25°	0.000±0.05	Richard	2026-04-23
0.00°±0.5°	0.00±0.10	CHECKED	DATE
0.0°±1°	0.0±0.20	Richard	2026-04-23
0°±2°	0±0.50	APPROVER	DATE
ANGULAR	LINEAR	Richard	2026-04-23
TOLERANCE		SCALE	
		1:1	

A	First Issue		Richard	Richard	2026/4/23
ISS	DESCRIPTION	GRID	DRW.	APP.	DATE



HIGHLY ELECTRIC CO.,LTD.

Fl.10-3, No. 738, Chung Cheng Road,  
Zhonghe District New Taipei City, Taiwan  
TEL:886-2-8226-1490 FAX:886-2-8226-1600

TITLE	Switch Lock
-------	-------------

FINISH	
--------	--

MATERIAL:	
-----------	--

Material must conform to RoHS Directive

PART NO.	S286A-2
----------	---------

DWG NO.	S286A-2	A4
---------	---------	----