


Warystory typu JVR-7N

SPECIFICATION

Part No	Maximum allowable Voltage		Maximum Energy		Withstanding Surge Current		Rated Wattage (W)	Varistor Voltage V1mA (V)	Maximum Clamping Voltage V5A (V)	Typical Capacitance (reference) @1KHz (pF)
	ACrms (V)	DC (V)	(10/1000us) (J)	(2ms) (J)	1 time (A)	2 times (A)				
WA 07N0820k	510	670	67.2	48.0	1200	600	0.25	820(738-902)	1355	60
WA 07N0780k	485	640	67.2	48.0				780(702-858)	1290	65
WA 07N0750k	460	615	67.2	48.0				750(675-825)	1240	65
WA 07N0680k	420	560	61.6	44.0				680(612-748)	1120	75
WA 07N0620k	385	505	61.6	44.0				620(558-682)	1025	80
WA 07N0560k	350	460	56.0	40.0				560(504-616)	920	90
WA 07N0510k	320	415	56.0	40.0				510(459-561)	845	100
WA 07N0470k	300	385	56.0	40.0				470(423-517)	775	105
WA 07N0430k	275	350	50.4	36.0				430(387-473)	710	115
WA 07N0390k	250	320	46.2	33.0				390(351-429)	650	130
WA 07N0360k	230	300	42.0	30.0				360(324-396)	595	140
WA 07N0330k	210	275	37.8	27.0				330(297-363)	550	150
WA 07N0300k	190	250	35.0	25.0				300(270-330)	500	165
WA 07N0270k	175	225	32.2	23.0				270(243-297)	455	185
WA 07N0240k	150	200	28.0	20.0				240(216-264)	395	210
WA 07N0220k	140	180	28.0	20.0				220(198-242)	360	230
WA 07N0200k	130	170	25.2	18.0				200(185-225)	340	250
WA 07N0180k	115	150	18.2	13.0				180(162-198)	300	280
WA 07N0150k	95	125	16.8	12.0				150(135-165)	250	330
WA 07N0120k	75	100	14.0	10.0				120(108-132)	200	420
WA 07N0100k	60	85	11.6	8.3				100(90-110)	165	500
WA 07N0082k	50	65	9.8	7.0	250	125	0.02	82(74-90)	135	600
WA 07N0068k	40	56	7.3	5.2				68(61-75)	#135	740
WA 07N0056k	35	45	6.2	4.4				56(50-62)	#110	890
WA 07N0047k	30	38	5.0	3.6				47(42-52)	#93	1100
WA 07N0039k	25	31	4.2	3.0				39(35-43)	#77	1300
WA 07N0033k	20	26	3.5	2.5				33(30-36)	#65	1500
WA 07N0027k	17	22	2.8	2.0				27(24-30)	#53	1800
WA 07N0022k	14	18	2.4	1.7				22(18.7-26)	#43	2300
WA 07N0018L	11	14	2.1	1.5				18(14.4-21.6)	#36	2800

DIMENSIONS

DIMENSIONS(mm)	Model No.	T MAX.	D MAX.	H MAX.	d.	E±0.8	L MIN.
	WA 07N0018L	4.5	9	12	0.6	5	20
	WA07N0068k						
	WA 07N0082k	4.1	9	12	0.6	5	20
	WA07N0470k	6.0					
	WA 07N0510k	6.4	9	12	0.6	5	20
	WA 07N0820k	7.9					