

UT50D



[Enlarge](#)



Registered Design No.: 0211977.6M003

[Download Manual](#)

Modern Digital Multimeters

SPECIFICATIONS

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	$\pm (0.5\%+1)$
AC Voltage	2V/20V/200V/750V	$\pm (0.8\%+3)$
DC Current	2mA/200mA/20A	$\pm (0.8\%+1)$
AC Current	20mA/200mA/20A	$\pm (1\%+3)$
Resistance	200W/2kW/200kW/2MW/20MW	$\pm (0.8\%+1)$
Capacitance	20nF/200nF/2mF/100mF	$\pm (2.5\%+5)$
Temperature (°C)	-40°C ~ 1000°C	$\pm (1\%+3)$
Inductance	2mH/20mH/200mH/20H	$\pm (2\%+10)$
Special Functions		
Diode		✓
Continuity Buzzer		✓
Data Hold		✓
Display Backlight	Auto Sensor	✓
Full Icon Display		✓
Sleep Mode		✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	Around 10MW	✓
Max. Display	1999	✓

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	59 x 25mm
Product Colour	Red and Grey
Product Net Weight	275g
Product Size	165 x 80 x 38.3mm
Standard Accessories	Test Lead, Battery, English Manual, Point Contact Temperature Probe, Test Clip
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40pcs
Standard Carton Measurement	598 x 418 x 340mm (Around 0.085 CBM Per Standard Carton)
Standard Carton Gross Weight	21kg

Specifications and other information are subject to change without further notice.

[Back to main menu](#)