

STM



Blindstopfen

Werkstoff
Gewinde

Messing vernickelt
Metrisch nach EN 60423 oder
PG nach DIN 40430

Blind plug

Material
Thread

Nickel-plated brass
Metric acc. to EN 60423 or
PG acc. to DIN 40430

STM-M

Artikel-Nr. STM-M	Gewinde EN 60423	Gewinde- länge mm	Kopf Ø mm	Packung Stück	Gewicht kg 100 Stück ca.
Article no. STM-M	Thread EN 60423	Length of thread mm	Head Ø mm	Packet Units	Weight kg 100 units approx.
Metr.					
0550.001.012	M 12 x 1,5	5,0	16,0	100	0,40
0550.001.016	M 16 x 1,5	6,0	20,0	100	0,52
0550.001.020	M 20 x 1,5	6,5	22,0	100	0,60
0550.001.025	M 25 x 1,5	7,0	28,0	100	0,91
0550.001.032	M 32 x 1,5	8,0	35,0	50	1,29
0550.001.040	M 40 x 1,5	8,0	45,0	50	2,10
0550.001.050	M 50 x 1,5	9,0	55,0	25	4,20
0550.001.063	M 63 x 1,5	10,0	68,0	10	8,60

STM-P

Artikel-Nr. STM-P	Gewinde DIN 40430	Gewinde- länge mm	Kopf Ø mm	Packung Stück	Gewicht kg 100 Stück ca.
Article no. STM-P	Thread DIN 40430	Length of thread mm	Head Ø mm	Packet Units	Weight kg 100 units approx.
PG					
0550.000.007	7	5,0	14,0	100	0,35
0550.000.009	9	6,0	17,0	100	0,55
0550.000.011	11	6,0	20,0	100	0,80
0550.000.013	13,5	6,5	22,0	100	0,95
0550.000.016	16	6,5	24,0	100	1,10
0550.000.021	21	7,0	30,0	100	2,10
0550.000.029	29	8,0	39,0	50	3,60
0550.000.036	36	9,0	50,0	25	7,30
0550.000.048	48	10,0	64,0	10	10,80